

megaSun[®] 5600

Technical data

megaSun 5600	Super	Super Power	Ultra Power
Tubes Canopy	24 x 100 W 2 x 80 W (p2)	24 x 160 W 2 x 80 W (p2)	24 x 160 W 2 x 80 W (p2)
Tubes Bed	16 x 120 W	16 x 120 W	16 x 180 W
Facial tanner	4 x 280 W (EU) 4 x 280 - 458 W (non EU)	4 x 280 W (EU) 4 x 280 - 458 W (non EU)	4 x 280 W (EU) 4 x 280 - 458 W (non EU)
Nominal power (with air conditioning)	7000 W (8300 W)	7900 W (9200 W)	8600 W (9900 W)
Air discharge	Exhaust-air socket: Ø 300 mm – 2.095 mm (top)		
Minimum capacity (exhaust air)	2.250 m ³ /h	2.250 m ³ /h	2.250 m ³ /h
Fuses K-type with safety cut out (3-pole)	3 x 25 A + FI (RCD)	3 x 25 A + FI (RCD)	3 x 25 A + FI (RCD)
electronicPower eP	standard	standard	standard
ACS	standard	standard	standard
fourSeasons	standard	standard	standard
megaVoice	optional	optional	optional
musicVibration	optional	optional	optional
mp3-sound-box + audio-connection	optional	optional	optional
automatic VolumeControl	optional	optional	optional
evoSystem²	standard	standard	standard
p2-Pigment tube	standard	standard	standard
aquaCool	optional	optional	optional
aroma	optional	optional	optional
airCon	optional	optional	optional
easyCare	optional	optional	optional
central exhaust air socket	optional	optional	optional
Extract air hose	optional	optional	optional
Warm air return circuit	optional	optional	optional
megaTimer	optional	optional	optional
Dimensions (h x w x d):	1480 mm x 2330 mm x 1610 mm (closed) 1800 mm x 2330 mm x 1440 mm (opened)		
Weight:	ca. 570 kg		

The rights to technical and design alterations are reserved.

KBL-Solarien AG · Sunshine Company · Ringstraße 24-26 · 56307 Dernbach · Germany
fon +49(0)2689.9426-0 · fax 9426-66 · eMail megaSun@kbl.de · www.megaSun.de